



■ Amplifier

- Audio output power.....120W+120W(8Ω)
- Total harmonic distortion(1KHz,-3dB,8Ω).....0.05%
- Audio input(sensitivity/impedance)
- MIC.....3.5mV/3.3KΩ
- MUSIC....350mV/33KΩ

■ Audio output (level/impedance)

- PRE-OUT.....2.8V/1KΩ
- Overload Output Voltage....9.6V/1KΩ
- SUB OUT(Balance)....5.2V/1KΩ
- Recording output.....340mV/1KΩ

PRE OUT(Balance) only DSP-8000 model

- L/R.....2.8V/1KΩ
- SL/SR.....2.8V/1KΩ
- CENTER....2.8V/1KΩ

■ Frequency response

- MIC....20Hz~15KHz,-0.2~-1dB
- MIC LOW CUT.....20Hz~1KHz
- MUSIC.....20Hz~20KHz,-1~0.5dB

■ Tone control response

- MIC BASS.....+9~-11dB(100Hz)
- GAIN.....+11.5~-13.5dB(1KHz)
- FREQ.....95~4KHz
- TREBLE.....+6.5~8.5dB(10KHz)
- LOW CUT.....20~1KHz(-18dB)

- MUSIC BASS.....±8.5dB(100Hz)
- TREBLE.....±9.5dB(10KHz)
- BBE-LOW.....+8(100Hz)
- BBE-HIGHT.....+9(10KHz)

■ Speaker Impedance(A/B)

- Music key control range.....11Step+-2.5Pitch
- Video input(sensitivity/input impedance).....1Vp-p/75Ω
- Video output(output level/output impedance)....1Vp-p/75Ω
- Echo delay time (MAX).....300ms
- Echo repeat time (MAX).....5Sec
- Reverb delay time (MAX).....10Sec

■ Power Supply

- Power supply.....110/120 VAC 50~60Hz
- 220/240VAC 50~60Hz
- Power consumption.....120W X 2

Other

- Dimensions(WxHxD)....430x136x415mm
- Weight.....13kg

Accessories

- Remote control unit(RC480).....x1
- Dry cell batteries(UM-4).....x2
- User Guide.....x1
- Power Core.....x1
- Warranty.....x1

Specifications Subject to change without prior notice.

